



ASTM / ASME A182/SA182 - Threaded to ANSI B1.20.1

Slip-On Flanges	Size - OD"	Bolt Boles	Dia. Of Holes	C	X	B	Y	Weight Ea. /lbs.	304ss Item Number	316ss Item Number
	1/2"-3.500"	4	0.62	0.50	1.38	0.88	0.56	2.00	A3460808	A3560808
	3/4"-3.875"	4	0.62	0.56	1.69	1.09	0.56	2.00	A3460812	A3560812
	1"-4.250"	4	0.62	0.62	2.00	1.36	0.62	2.00	A3460816	A3560816
	1 1/4"-4.625"	4	0.62	0.69	2.50	1.70	0.75	3.00	A3460820	A3560820
	1 1/2"-5.000"	4	0.62	0.75	2.88	1.95	0.81	3.00	A3460824	A3560824
	2"-6.000"	4	0.75	0.81	3.62	2.44	0.94	5.00	A3460832	A3560832
	2 1/2"-7.000"	4	0.75	0.94	4.12	2.94	1.06	7.00	A3460840	A3560840
	3"-7.500"	4	0.75	1.06	5.00	3.57	1.12	8.00	A3460848	A3560848
	4"-9.000"	8	0.78	1.19	6.19	4.57	1.25	13.00	A3460864	A3560864
	5"-10.000"	8	0.88	1.31	7.31	5.66	1.38	15.00	A3460870	A3560870
	6"-11.000"	8	0.88	1.38	8.50	6.72	1.50	19.00	A3460872	A3560872
	8"-13.500"	8	0.88	1.56	10.62	8.72	1.69	30.00	A3460884	A3560884